N.B.S. FORMAT SPECIFICATION



UNIVERSAL LOUVRE - 1UL/SH

Company:	ALPS Ltd Downley Road HAVANT Hampshire PO9 2NJ Tel. 02392 480055 Fax. 02392 480099
Contact	info@alpslouvres.co.uk (tel: 02392 480055)
Product Reference	UNIVERSAL LOUVRE TYPE 1UL/SH
Material	All principal components manufactured from: Aluminium alloy type 3005 (Colterra) - please also see Alternative Materials below.
Blade pitch and angle	50mm @ 45 degrees
Number of louvre banks	1 (Single bank)
Special Features	Louvre blades shall be roll formed to an aerodynamically efficient profile and clipped to concealed structural supporting mullions. The system shall achieve a minimum aerodynamic performance coefficient (Cv) of 0.435 (inlet) with bird mesh fitted to the rear.
	HEVAC Weathering Classification Class D
Decorative Finish	Decorative finish: Mill finish (unpainted) / Stoved polyester powder paint (from ALPS standard colour chart) / Natural (silver) anodised / Colour anodised (Anolok) / Blue grey anodised (Anolok II).
Coverage	Partial (blades, head frame, jamb frames and cills are painted. Remaining items will be mill finish - unpainted) / Total (all principle components are painted).
Accessories	Optional extras (additional cost): Bird Guards / Insect Mesh / Blanking Panel / Insulated Blanking Panel / Mitred Corners / Louvred Doors.
Alternative Materials	Optional extras (additional cost): Galvanised Mild Steel / Stainless Steel.